## TECHNICAL DATA SHEET



## **AF 100** 100% active silicone defoamer

Description

CHT USA's 100% active defoamers are formulated to control foam in a wide variety of industrial processes.

Key Features

Excellent foam knockdown and persistence

Effective in low concentrations

Effective in hot and cold systems

Easy to handle

**Key Applications** 

Coatings

Food starch and protein washes

Pulp and paper

Waste water treatment

**Application** 

AF 100 is used in to control foam in industrial applications including coatings, oil and gas, food starch and protien washes, beverages, pulp and paper and waste water treatment.

**Use and Cure Information** 

100% active silicone defoamers can be dispersed with minimal agitation in most nonaqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

Method Value **Property** 

Product

% actives 100 % Appearance Liquid

Color Greyish white

Viscosity (cst) 3000

**Addition Rates** 

Dosage - 1

As defined by FDA regulation

21 CFR 173.340, defoaming

agents used in processing

foods.

100-10,000ppm active in Dosage - 2

industrial applications.

Storage

40 °C / 104 °F Max Storage Temperature

This product is available for Packaging

sale as 40 lb. pails and 441 lb. drums. and 2205 lb. totes

Shelf Life 12 mths

**Health & Safety** 

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

This product is not intended for pharmaceutical use.

21 Sep 2021 **Revision Date** 

Revision No

Download Date 17 May 2024