## TECHNICAL DATA SHEET



# EM 1407 40% Active Emulsion of a High Molecular Weight Polydimethylsiloxane

Method Value Description **Property** This product is an industrial anionic polydimethylsiloxane

emulsion **Product Key Features** Appearance White liquid Long lasting Ionicity **Anionic** 

Effective in low concentrations Solids Content (%) 42 % Excellent wetting/spreading on surfaces 8.0 Easily dispersed in water with minimal agitation

**Key Applications Addition Rates** 

Release agent Dosage - 1 0.1 - 1% Auto care

Storage Rubber treatment Max Storage Temperature 40 °C / 104 °F **Application** 

40 lb. pails, 441 lb. drums, EM-1407 is a 40% active emulsion of a high molecular weight Packaging 2205 lb. totes, and tanker silicone polymer. The high molecular weight dimethicone actives

Shelf Life are delivered in an opaque, low viscosity liquid with neutral pH. This emulsion was developed as an effective release agent at

low concentrations. EM 1407 is a superior release agent, but has exceled in a wide variety of applications including, hydrophobic coatings, leather conditioning, and automotive care.

### **Use and Cure Information**

Leather conditioning

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

### Limitations

This product is not intended for pharmaceutical use.

**Revision Date** 03 Jan 2024

Revision No 11

Download Date 17 May 2024