

## HANSA CARE 9040 D Modified siloxane as an ingredient for Home and Car Care.

### Description

The silicone hybrids are special silicone polymers combined with the organic polymer chemistry. Therefore it is possible to create with these polymers unique and outstanding effects in home-, fabric- and car care products.

### Key Features

- Water repellency
- Durability
- Enhances Gloss and Color depth
- Smoothness

### Key Applications

- Car Polishes
- Leather Care
- Vinyl and Tyre Care

### Application

HANSA CARE 9040 D can be used in car polishes to improve water repellency, durability and gloss. The product is also suitable to formulate polishes or wax formulations for other surfaces e.g. vinyl and tyre.

### Use and Cure Information

Stir before use.

### Health & Safety

Safety Data Sheets available on request.

### Packaging

Drums and bulk containers. Please contact our sales department for more information.

Revision Date 01 Dec 2022  
Revision No 2  
Download Date 17 May 2024

### Property

#### Product

Appearance

Chemistry

Ionicity

MIT Free

Non-Volatile Content (%)

Ultralow cyclic content

Viscosity

#### Addition Rates

Dosage - 1

Dosage - 2

#### Storage

Max Storage Temperature

Min Storage Temperature

Shelf Life

### Test Method

### Value

Colorless to yellow liquid

Alkylaminofunctional siloxane

Cationic

Yes

Approx. 100

Yes

Brookfield 500 – 1,500 cP

1.0 - 5.0% in polishes

1.0 - 10.0% in vinyl and tyre care

40 °C / 104 °F

4 °C / 39 °F

12 mths

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: [info@cht.com](mailto:info@cht.com), Homepage: [www.cht.com](http://www.cht.com) / [www.cht-silicones.com](http://www.cht-silicones.com)