

## HANSA CARE HTC

### Inorganic/Organic polymer based on Si-Ceramic-Sol-Gel Chemistry as an ingredient for Home and Car Care products.

#### Description

Silicone resins are reactive polymers to enhance durability and water repellency of many formulations. The Silicone resins can be used in combination with reactive Aminosiloxane to formulate high quality sealants for car care or long lasting impregnation agent for mineral surfaces. Further applications of Silicone resins are car polishes, spray waxes, impregnation agents for kitchen worktops and for wood.

#### Key Features

- Very easy to apply and suitable for do-it-yourself application
- Forms a transparent hard and semi-flexible film
- Excellent resistance with good adhesion
- Hydrophobic

#### Key Applications

- Glass sealants
- Plastic sealant
- Car sealants

#### Application

For optimum performance, we recommend non-polar solvents such as aliphatic hydrocarbons, isododecane or D5. If polar solvents are required, anhydrous isopropanol, which can be combined with the non-polar solvent, is recommended. Lasts on glass 2-6 months depending on weather conditions and washing cycles.

#### Health & Safety

Safety Data Sheet available on request.

#### Packaging

Drums. Please contact our sales department for more information.

Property	Test Method	Value
<b>Product</b>		
Appearance		Clear fluid
Chemistry		Silicone resin
Ionicity		Non-ionic
MIT Free		Yes
Non-Volatile Content (%)		95
Ultralow cyclic content		Yes
<b>Addition Rates</b>		
Dosage - 1		High end sealants 20-70%
Dosage - 2		Easy to use sealants 10 - 30%
<b>Storage</b>		
Max Storage Temperature		40 °C / 104 °F
Shelf Life		12 mths

Revision Date      10 Jan 2024  
Revision No        19  
Download Date     17 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com