## **TECHNICAL DATA SHEET**



## HANSA MBC 37180 Mixture of OH-PDMS and reinforcing filler for producing condensation crosslinking silicones

Description Property Test Method Value

CHTs masterbatches are a mixture of silica and polysiloxane. Addition of the masterbatch is a convenient method of incorporating silica into an elastomer formulation to increase physical properties. The values for tensile, tear, and elongation typically increase commensurately with additional silica. Masterbatchs are typically suited specifically for condensation or addition cure chemistries. The compositions are solvent-free and typically low in cyclic siloxane content.

 Product

 Color
 Transparent

 Non-Volatile Content (%)
 > 99

 Shelf Life
 12 mths

 Ultralow cyclic content
 Yes

 Viscosity
 Brookfield HTBD,
 600000 cP

Key Features

• containing silica

Uncured Product

Cure Type Condensation cure

**Cured Product** 

Density DIN 53479 **1.19 g/cm3** 

Solubility

Solubility - Water insoluble

Key Applications

translucent

Intermediate for condensation curing formulations

Use and Cure Information

containing OH-Siliconepolymer

good mechanical properties

Masterbatches are typically high viscosity and non-flowing. One must incorporate siloxane polymers of the appropriate chemistry

and viscosity profile to result in a flowable composition. Curing can be obtained with the addition of an appropriate crosslinker and catalyst system.

## **Health & Safety**

Please observe our safety data sheets and the safety remarks on our container labels when handling our products. The dangerous goods regulations and the accident prevention regulations of the professional associations must be particularly observed. Keep the EC safety data sheet of the applied product at hand since it provides you with useful instructions for the safe use and disposal of the product as well as for actions to be taken in case of accidents.

Revision Date 21 Feb 2023

Revision No

Download Date 17 May 2024