TECHNICAL DATA SHEET



36 mths

ICM SF 725P 50% Active Aminofunctional Polydimethylsiloxane

| Description This product is an industrial amine functionalized | Property | Test Method | Value |
|--|--|----------------|--------------------------------|
| polydimethylsiloxane polymer. | Product | | |
| Key Features | % actives | | 50 % |
| Detergent Resistant | Amine Number | | 25 |
| Long Lasting Shine improved water repellency | Appearance | | Clear to yellow liquid |
| improved water repellency Soluble in many organic solvents Key Applications Automotive care Polishing applications | Density | BS ISO 2781 | 0.87 g/cm3 |
| | Non-Volatile Content (%) Ultralow cyclic content | | 50 |
| | | | no |
| Mold release | Viscosity (cst) | | 70 |
| Textiles | , , , | | |
| Application | Storage | | |
| ICM SF 725P is a 50% active Aminofunctional | Max Storage Temperature | | 40 °C / 104 °F |
| Polydimethylsiloxane. It uses the polar nature of Aminofunctional | Min Storage Temperature | | 4 °C / 39 °F |
| silicones to cause a film to deposit and adhere to surfaces including paint, chrome, aluminum and textiles. | Packaging | | 35 lb. pails and 353 lb. drums |

Use and Cure Information

This product is soluble in a wide variety of organic solvents and can be incorporated into the oil phase of a final formulation.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Shelf Life

Limitations

This product is not intended for pharmaceutical use.

Revision Date 08 Jul 2022 Revision No 13

Download Date 17 May 2024