

TECHNICAL DATA SHEET

TE-352 FG

TE-352 FG is a 40% active food grade emulsion of 350 cSt PDMS fluid. This product was specially formulated for food packaging applications

Description

This product is a food grade emulsion of a polydimethylsiloxane fluid.

Key Features

- alkylphenol and formaldehyde free. Solvent free and chemical inert.
- Excellent wetting/spreading. Improved deposition on surfaces. Good lubricity at low concentrations. High dilution stability. Excellent freeze thaw stability.
- Emulsifier type: Nonionic and anionic

Key Applications

- De-nesting of plastics used in the thermoforming process
- Suitable for amorphous polyester (APET), polyvinylchloride (PVC), and polypropylene (PP)

Application

Designed specifically for de-nesting of plastics used in the thermoforming process. Suitable for amorphous polyester (APET), polyvinylchloride (PVC), and polypropylene (PP).

Use and Cure Information

This product can be diluted in water or an aqueous media before use. If unsure where to start the dilution, it is recommended to dilute one-part product to 30 parts water/aqueous media. This dilution is then applied to the food contact surface by spraying, wiping, brushing, or dipping.

Health & Safety

This product is not intended for pharmaceutical use. It is the responsibility of the user to ensure acceptable compatibility with intended food contact surfaces.

Property

Product

% Silicone

Appearance

FDA Tested

pH

Solubility

Solubility - Water

Storage

Max Storage Temperature

Packaging

Shelf Life

Test Method

Value

40 %

blue/white creamy liquid

CFR (21)
177.2600

yes: 175.300, 176.170,
177.2600, 178.3400 and
181.28

4

yes. with light mixing until
solution is homogenous

40°C °C / 104 °F

This product is available for
sale as 40 lb. pails and 441
lb. drums. and 2205 lb. totes
12 mths

Revision Date 22 Sep 2021
Revision No 4
Download Date 17 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com